



Rated Line Pull	9500lbs(4310kgs)
Winch Motor	Series wound 5.7hp/4.2kw 12V
Control	Remote Control
Gear Train	3-Stage Planetary
Gear Reduction Ratio	216:1
Clutch	Sliding Ring Gear
Brake Action	Automatic in drum
Drum Diameter	64mm
Drum Length	226mm
Steel Cable	Dia 8.3mmx28m
Fairlead	4-Way Roller Fairlead
Remote Control	Included
Battery	650CCA min. for winching
Battery Leads	25mm ² x1.8m
Dimensions	552mm l.x160mm d.x194mm h.
Mounting Bolt Pattern	254mm x 114.3mm
Weight	84lbs(38kgs)

Line Speed / AMP Draw (First Layer)							
Line	lbs	No	2000	4000	6000	8000	9500
Pull	kg	Load	907	1814	2722	3629	4310
Line Speed	ft/min	35.4	17.1	13.0	9.79	8.01	6.9
	m/min	10.8	5.2	3.98	2.98	2.44	2.1
Motor	Amps 12V	80	140	200	260	310	350

9500 lbs Line Pull and Cable Capacity						
Layers of Cable		1	2	3	4	
Rated Line Pull Per Layer	lbs	9500	8000	7200	6000	
	kg	4310	3629	3266	2994	
Cable Capacity Per Layer	ft	19.6	43	72	92	
	m	6.0	13.2	22	28	

TYREX WINCH 9500 LB